
**GUTEX Thermoflex - dim. 135 x 57.5 cm**  
**GUTEX Thermoflex - Dim. 135 x 57.5 cm**


Lambda	0.036
I-I / BKZ	E/RF3 cr
kg / m <sup>3</sup>	50

Art. Nr.	Epaisseur Stärke	Paq./pal. Pak./Pal.	Pces/paq. Stk/Pak.	Pces/pal. Stk/Pal.	m <sup>2</sup> /palette m <sup>2</sup> /Palette	Fr./m <sup>2</sup>
11.131	40 mm	14	8	112	86.94	6.70
18.532	50 mm	10	9	90	69.86	8.00
11.132	60 mm	10	8	80	62.10	9.60
11.133	80 mm	10	6	60	46.58	12.30
11.135	100 mm	12	4	48	37.26	15.00
11.134	120 mm	10	4	40	31.05	17.70
11.136	140 mm	8	4	32	24.84	20.50
11.137	160 mm	10	3	30	23.29	23.50
11.138	180 mm	8	3	24	18.63	26.60
11.139	200 mm	12	2	24	18.63	32.00
14.647	220 mm	10	2	20	15.53	34.20
17.493	240 mm	10	2	20	15.53	37.30


**GUTEX Thermofloor - dim. 120 x 60 cm**  
**GUTEX Thermofloor - Dim. 120 x 60 cm**


Lambda	0.042
I-I / BKZ	E/RF3 cr
kg / m <sup>3</sup>	160
NM/m <sup>3</sup>	≤ 30

Art. Nr.	Epaisseur Stärke	Pces/paq. Stk/Pak.	Pces/pal. Stk/Pal.	m <sup>2</sup> /palette m <sup>2</sup> /Palette	Fr./m <sup>2</sup>
11.149	21/20 mm		180	129.60	7.80
11.150	31/30 mm		120	86.40	11.60


**GUTEX Happy Step - dim. 86 x 59 cm**  
**GUTEX Happy Step - Dim. 86 x 59 cm**




Lambda	0.046
I-I / BKZ	E/RF3 cr
kg / m <sup>3</sup>	260
kPa	≥ 100

Art. Nr.	Epaisseur Stärke	Pces/paq. Stk/Pak.	Pces/pal. Stk/Pal.	m <sup>2</sup> /palette m <sup>2</sup> /Palette	Fr./m <sup>2</sup>
11.130	6 mm	20	640	324.74	3.30


**GUTEX Standard N - panneau de fibre de bois mou - dim. 250 x 100 cm**  
**GUTEX Standard N - Holzweichfaser-Platte - Dim. 250 x 100 cm**


Lambda	0.048
I-I / BKZ	E/RF3 cr
kg / m <sup>3</sup>	250
kPa	≥ 100

Art. Nr.	Epaisseur Stärke	Pces/pal. Stk/Pal.	m <sup>2</sup> /palette m <sup>2</sup> /Palette	Fr./m <sup>2</sup>
17.077	8 mm	130	325.00	3.10
17.078	10 mm	100	250.00	3.70
17.079	12 mm	80	200.00	4.30
17.080	15 mm	70	175.00	5.50
17.584	18 mm	55	137.50	6.60


**STEICO therm SD - Isolant phonique - dim. 1350 x 600 mm**  
**STEICO therm SD - Trittschalldämmung - Dim. 1350 x 600 mm**


Lambda	0.038
I-I / BKZ	E/RF3 cr
kg / m <sup>3</sup>	160

Art. Nr.	Epaisseur Stärke	Spécification Spezifikation	pnx/pal. Platten/Pal.	m <sup>2</sup> /palette m <sup>2</sup> /Palette	Fr./m <sup>2</sup>
19.571	20 mm	bords droits	116	93.96	4.66
19.572	40 mm	rundum stumpfkantig	74	59.94	7.02